

PSSO®

Amplificateur QCA-10000 4 canaux SMPS

Class I Amplificateur PA stéréo à alimentation à découpage,
4 x 2500 W RMS (2 Ohm), 4 x 2100 W RMS (4 Ohm)

Réf. : 10451697

GTIN: 4026397513370



L'article n'est plus disponible.

PSSO®

Amplificateur QCA-10000 4 canaux SMPS

Class I Amplificateur PA stéréo à alimentation à découpage,
4 x 2500 W RMS (2 Ohm), 4 x 2100 W RMS (4 Ohm)

Réf. : 10451697

GTIN: 4026397513370

Caractéristiques:

- 4-channel PA amplifier with class I circuitry
- 4 x 2100 W/4 ohms
- Low weight and height due to integrated switch mode power supply
- Reliable power amp with high impulse stability for a wide range of applications (e.g. compact PAs, multi-way PAs, concerts)
- 3 operating modes can be selected (stereo, parallel or bridged)
- 4 level controls for precise level adjustment
- Input sensitivity adjustable
- LED VU meter and LEDs for activated protective circuit (protect), overload (clip), and signal per channel
- Speaker switch-on delay
- Complete protection set against short-circuit, overheat, clipping, overload, DC voltage and VHF signals
- Electronically balanced inputs via XLR mounting jacks, with XLR feed-through outputs
- Speaker outputs via lockable speaker jacks