

## OMNITRONIC CMP-2001 Single CD/MP3 Player

CD/MP3 player with recording function for DJs

Réf. : 10602411

GTIN: 4026397565171



**L'article n'est plus disponible.**

### Caractéristiques:

- Audio CD/CD-R/CD-RW/MP3 CD
- 2 USB 2.0 ports for USB storage media (FAT 16/32)
- Recording from CD to USB medium (adjustable bit rate 32-320 kbit/s)
- Supplied with infrared remote control
- Access music files more easily and quickly via smart music database management with free PC software Database Builder
- Sort USB devices lightning-fast by title, artist, album and genre
- System menu for user-defined settings
- 20 seconds anti-shock protection
- Outstanding reading time of the files (instant start within 10 ms)
- Automatic beat counter (switchable to manual operation)
- Master tempo (tonal pitch remains constant when speed is changed)
- Alphanumeric LCD with ID3 tag indication
- Easy-turning jog dial (fast or frame search and pitch bend)
- Pitch adjustment  $\pm 4\%$ ,  $\pm 8\%$ ,  $\pm 16\%$ ,  $\pm 100\%$  (MP3 CD  $\pm 16\%$ )
- Folder navigation
- Pitch bend buttons
- Cue/auto cue function
- Seamless loop/reloop
- Single or continuous play
- Repeat function
- Indication of elapsed time, remain time (MP3 files) or total remain time (audio CD)
- Bargraph display
- Pitch adjustment is displayed in %
- Rubber buttons with color illumination
- Drives are locked in play mode

### Logistique

EAN / GTIN: 4026397565171

Poids: 5,21 kg

Longueur: 0.53 m

Largeur: 0.33 m

Hauteur: 0.17 m

- Rack installation, 2 U
  - The Database Builder software is available on the manufacturer's product page
  - Processeur de signal numérique Mastertempo
  - Commandé via Télécommande infrarouge
  - Samplingrate: 44,1 kHz
  - Réglage du niveau: CD-DA  $\pm 4\%$ ,  $\pm 8\%$ ,  $\pm 16\%$ ,  $\pm 100\%$
  - Réglage du niveau: MP3  $\pm 4\%$ ,  $\pm 8\%$ ,  $\pm 16\%$
  - (19") 48,3 cm installation en rack 2 HE
- L'étendue des fournitures**
- 1 x télécommande

## Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	13 W
Branchement électrique:	Alimentation électrique via Appareils froids (M) version encastrable Câble d'alimentation à prise contact de protection (inclus dans la livraison)
Plage de fréquence:	17 - 20000 Hz
Rapport signal/bruit:	>126 dB
Distorsion harmonique:	<0,008 % avec 1 kHz
DSP:	Processeur de signal numérique Mastertempo
Commande:	Télécommande infrarouge
Lecteur audio:	Lecteur USB + CD, (ID3 tag), Anti-choc, Seamless loop
Samplingrate:	44,1 kHz
Lecteur de CD-ROM:	Tiroir-Lecteur individuel
Écran:	CD-DA ID3-Tags , Temps de lecture du titre , Temps de lecture du titre restant , Temps de lecture restant total; MP3 ID3-Tags , Temps de lecture du titre , Temps de lecture du titre restant
Connexions:	Sortie: Line via RCA stéréo 2 V Sortie: Line via XLR 3 broches 2 V
Format de la musique:	CD, CD-R, CD-RW, CD-DA, MP3; WAV
Précision du châssis:	1/75 s
Appareils de stockage appropriés:	Appareils USB max. 32GB (FAT 32)
Réglage du niveau:	CD-DA $\pm 4\%$ , $\pm 8\%$ , $\pm 16\%$ , $\pm 100\%$ MP3 $\pm 4\%$ , $\pm 8\%$ , $\pm 16\%$
Port USB:	2 x Typ A
Convertisseur:	8-fach/ 1 bit
Conception du boîtier:	(19") 48,3 cm installation en rack 2 HE
Dimension:	Largeur : 48,3 cm Profondeur : 27,3 cm Hauteur : 8,9 cm
Poids:	4,41 kg
Télécommande	
Batterie:	Pile bouton 3,0 V CR2025 lithium manganèse intégré