

**PSSO CSA-218A top, active, black**

Enceinte de sonorisation active professionnelle avec amplificateur Biamp, 230 W

Réf. : 11040817

GTIN: 4026397527650

**Caractéristiques:**

- Active full-range top speaker, qualified for suspension
- For permanent installations and touring purposes
- Class D biamp power amplifier (230 W)
- Efficient, light-weight switch mode power supply with energy saving mode
- Light-weight cabinet due to high-quality special plastic (9 kg only)
- Elegant housing design
- 20 cm (8") bass speaker and 3.5 cm (1.35") titanium compression horn driver
- 90° x 90° nominal coverage
- Balanced XLR input
- Speaker flange for mobile use included in the delivery
- PowerCon mains input
- Applications: as monitor, on a subwoofer or speaker stand, suspended
- Matching mounting brackets and flying hardware available as accessories

**Logistique**

EAN / GTIN: 4026397527650

Poids: 12,25 kg

Longueur: 0.56 m

Largeur: 0.37 m

Hauteur: 0.45 m

**Données techniques:**

|                          |                                    |
|--------------------------|------------------------------------|
| Alimentation électrique: | 100-240 V CA, 50/60 Hz             |
| Plage de fréquence:      | 70 - 18000 Hz                      |
| Enceinte:                | 1 x Boumeur 8"                     |
| Rated power:             | 230 W                              |
| Components:              | HF: 3.5 cm (1.35"), LF: 20 cm (8") |
| Crossover frequency:     | 2.5 kHz                            |

|                      |  |
|----------------------|--|
| Dispersion angle:    | 90° x 90°                                  |
| Maximum SPL:         | 113 dB                                     |
| Acoustic loading:    | Bassreflex                                 |
| Cabinet material:    | HIPS                                       |
| Amplifier:           | Class D                                    |
| THD:                 | <0.05 %                                    |
| S/N ratio:           | >80 dB                                     |
| Damping factor:      | >50  |
| Input sensitivity:   | 2 V  |
| Input impedance:     | 40 kohms/20 kohms (bal./unbal.)            |
| Signal input:        | XLR  |
| Power consumption:   | 350 W                                      |
| Protection circuits: | Limiter, overheat, overload, short-circuit |
| LED indicators:      | Power, clip                                |
| Weight:              | 10 kg                                      |

### **Contenu de la livraison:**

---