

PSSO CLA-228 MK2 LINE ARRAY Top

Top speaker, 2 x 8" woofer, 1.73" driver, MF: 300 W RMS, HF: 60 W RMS

Réf. : 11040901

GTIN: 4026397447477



Caractéristiques:

- Improved MKII version with BEYMA drivers
- Compact line array for permanent installations and touring purposes
- Time saving 2-man installation directly from the transport case
- Lightweight housing due to high-quality plastic
- Low weight of the whole construction and reduced demands for the flying points
- Elegant housing design for avoiding resonance and standing waves
- Two powerful 20 cm low/mid neodymium magnets (2 x 8")
- 4.4 cm neodymium driver (1.73") with titanium diaphragm
- Specially designed waveguide
- Maximum efficiency due to biamped control
- Wide horizontal dispersion angle of 100°
- Curving adjustable between 0° and 12°
- Easy rigging with captive quick release pins
- Tight locking pins eliminating vibration noise
- Flying hardware regularly tested by an independent and accredited testing institute

Logistique

EAN / GTIN: 4026397447477

Poids: 21,85 kg

Longueur: 0.78 m

Largeur: 0.37 m

Hauteur: 0.37 m

Données techniques:

Plage de fréquence: 68 - 20000 Hz

Sensibilité: 104 dB HF; 96 dB MF

Impédance: 4/8 Ohm Biamp

Fréquence de rupture: 1800 Hz

Dimension: Largeur : 67 cm

Profondeur : 28,5 cm
Hauteur : 28,5 cm

| | |
|-------------------|--|
| Poids: | 19,15 kg |
| MF rated power: | 300 W RMS |
| HF rated power: | 60 W RMS |
| MF program power: | 600 W |
| HF program power: | 120 W |
| Components: | 2 x 20 cm woofer (2 x 8"), 4.4 cm driver (1.73") |
| Connection: | 2 Speakon sockets (4-pin) |
| MF maximum SPL: | 123 dB |
| HF maximum SPL: | 124 dB |
| Impedance: | MF 16 ohms / HF 8 ohms |
| Dispersion angle: | H=100°, V=3° |

Contenu de la livraison:
