

## OMNITRONIC UHF-202 Wireless Mic System 863.42+864.99MHz

Système de microphone 2 canaux, technologie UHF-PLL

Réf. : 13063215

GTIN: 4026397478419



**L'article n'est plus disponible.**

### Caractéristiques:

- 2-channel receiver unit and 2 hand-held microphones with UHF PLL technology
- Operation in the low-interference UHF band (863-865 MHz) with 2 fixed frequencies
- Parallel operation of up to 4 transmission channels is possible without any interference
- 2 separate channels with volume controls and LEDs for carrier signal and audio signal
- Balanced XLR output per channel
- 6.3 mm jack for mixed signal output
- Jack cable included
- Microphones with mute switch and color caps for distinction on stage
- Matching pocket transmitters can be ordered separately
- License-free and approved in the EU

#### L'étendue des fournitures

- 1 x microphone

### Logistique

EAN / GTIN: 4026397478419

Poids: 1,36 kg

Longueur: 0.41 m

Largeur: 0.34 m

Hauteur: 0.07 m

### Données techniques:

|                                   |                                                             |
|-----------------------------------|-------------------------------------------------------------|
| Type:                             | Ensemble complet sans fil                                   |
| Puissance totale de raccordement: | 10,00 W                                                     |
| Plage de fréquence:               | 40 - 18000 Hz                                               |
| Dimension:                        | Largeur : 21 cm<br>Profondeur : 4,5 cm<br>Hauteur : 15,5 cm |

Microphone

|                     |                                                 |
|---------------------|-------------------------------------------------|
| Batterie:           | 4 x Mignon (AA) (non incluse dans la livraison) |
| System:             | Non-diversity, 2 channels                       |
| Carrier frequency:  | 863.420 MHz, 864.990 MHz                        |
| Coverage:           | 50 m (with line-of-sight)                       |
| RF power output:    | 10 mW                                           |
| Modulation method:  | F3F                                             |
| S/N ratio:          | >105 dB                                         |
| Selectivity:        | >80 dB                                          |
| T.H.D.:             | <0.5 % at 1 kHz                                 |
| Audio outputs:      |                                                 |
| Mic:                | 2 x XLR, bal.                                   |
| Level/impedance:    | 400 mV, 2.2 kohms                               |
| Line:               | 6.3 mm jack, unbal.                             |
| Level/impedance:    | 200 mV, 2.2 kohms                               |
| Power supply        |                                                 |
| Receiver:           | 100-240 V AC, 50/60 Hz via supplied power unit  |
| Dimensions, weight: |                                                 |
| Receiver:           | 155 x 210 x 45 mm (L x W x H), 455 g            |
| Microphones:        | 50 x 265 mm (D x L), 175 g                      |