



**L'article n'est plus disponible.**

### Caractéristiques:

#### EUROLITE DF-40 LED display 92x92

Ultra flat and flexible LED display

- Ultraflat and flexible LED display for bright and colorful projection of videos and graphics
- Bends, rolls and moulds around almost any shape for waves, columns, circles, arcs and angles
- 4 millimeters thin and 800 grams light for convenient transport and simple installation
- 40 mm pixel pitch (seamless image at about 40 m)
- Applicable for installation in counters, columns and rear walls in shops and clubs, on fairs and various other environments
- Extendable for of large video billboards
- Control per network protocol in live mode with PC software or in stand-alone mode with media player (accessories)
- Control also possible per MADRIX, DMX and Artnet
- Large operating range from -20° to +50° C
- 484 LED puissantes SMD 3in1 TCL RGB (mélange de couleurs homogène)
- Commandé via DMX

#### EUROLITE DF Control system

Control unit for DF-40 LED display

- Control unit and PC software for controlling DF-40 LED displays
- Operation with the handy media player (80503610) or a network-compatible computer
- Create stunning light shows for your displays with the included light effect software
- Load your shows onto the included SD memory card for playback on the media player
- Ethernet input and output, LAN cable included

### Logistique

## EUROLITE DF power unit

Mountable power unit for DF-40 LED displays

- Power unit in aluminum housing for DF-40 LED displays
- Each DF-40 LED display requires a separate power unit
- Screw terminals
- Short-circuit proof, overload-protected
- Protected against excess temperature

## EUROLITE DF Media player

Media player for DF-40 LED display

- Media player and control software for flexible use DF-40 LED displays
- Allows to run light shows and videos on your displays without the need for a computer
- Use your PC to create stunning light shows with the included light effect software
- Load your shows onto the included SD memory card for playback on the media player
- Four operating buttons for setting brightness, speed, color and playback mode
- 6 cm backlit display
- Ethernet connectors, LAN cable included

## Données techniques:

---

Poids: 6,45 kg

---

## EUROLITE DF-40 LED display 92x92

Puissance totale de raccordement: 40,00 W

---

LED: 484 x SMD 3in1 TCL RGB (mélange de couleurs homogène)

---

Commande: DMX

---

Dimension: Largeur : 92,5 cm  
Profondeur : 4 cm  
Hauteur : 92 cm

---

Poids: 600 g

---

Resolution: 22 x 22 pixels

---

Pixel pitch: 40 mm

---

Pixel configuration: tricolor RGB LEDs

---

Display mode: synchronous to PC, or asynchronous per media player

---

Brightness: R 250-1000 mcd, G 500-1650 mcd, B 80-500 mcd

---

Viewing angle: 120°

---

Data refresh rate: 400 cycles/sec

---

Colors: 16.7 million (R 256, G 256, B 256)

---

Operating temperature: -20° to 50°C

---

Dimensions (L x W x H): 925 x 920 x 4 mm

---

### Spécifications juridiques

Produit spécial: Non destiné à l'éclairage de la pièce dans les ménages

---

Utilisation: Éclairage pour effets de spectacle

---

#### **EUROLITE DF Control system**

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	10,00 W
Dimension:	Largeur : 16 cm Profondeur : 15,5 cm Hauteur : 5 cm
Poids:	1,10 kg
Signal input:	RJ45, CAT5e
Signal link:	RJ45, CAT5e
Number of displays:	max. 6 per control unit
Serial connection:	max. 255 control units for PC operation max. 48 control units for media player operation
Pixels:	max. 3072
Dimensions (L x W x H):	160 x 155 x 50 mm
System requirements:	Windows XP, Vista or 7 Separate network card (100 Mbps) SD card reader

#### **EUROLITE DF power unit**

Alimentation électrique:	100-240 V CA, 50/60 Hz
Dimension:	Largeur : 23 cm Profondeur : 15,5 cm Hauteur : 5 cm
Poids:	900 g
Output voltage:	5 V DC
Output current:	40 A
Dimensions (L x W x H):	230 x 155 x 50 mm

#### **EUROLITE DF Media player**

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	10,00 W
Dimension:	Largeur : 19 cm Profondeur : 14 cm Hauteur : 4 cm
Poids:	850 g
Signal output:	2 x RJ45, CAT5e
Storage medium:	SD memory card up to 2 GB (incl.)
Number of displays:	288 max.
Dimensions (L x W x H):	190 x 140 x 40 mm
System requirements:	Windows XP, Vista or 7

---

Separate network card (100 Mbps)

---

SD card reader

---