



L'article n'est plus disponible.

Caractéristiques:

EUROLITE LED Pixel Pole 50 cm

Barre de LED pour mappage de pixels

- Barre de LED de 16 ou 32 pixels pour les applications vidéo et de pixel mapping via Art-Net
- Distribution du signal par câble UTP
- Créez facilement des animations avec MADRIX ou tout autre logiciel supportant Art-Net
- 16 LED puissantes SMD 5050 3in1 TCL RGB (mélange de couleurs homogène)
commandé individuellement LEDs
- 30 programmes de spectacle intégrés
- Commandé via Accessoire; Fonction maître/esclave
- Avec un Angle de départ de 180°
- Pour des domaines d'application tels que: Agencement de salons et magasin; Clubs/Écoles de danse; Scène
- Mélange de couleurs en continu; Dimmer électronique
- Effet stroboscope

EUROLITE LED PSU-4A Artnet/DMX

Control unit for EUROLITE LED Pixel Poles

- Create sensational effects in conjunction with the decorative LED Pixel Poles
- Control via Art-Net/DMX
- For use with MADRIX or any other lighting control software supporting Art-Net
- Connections for 4 x 160 pixels
- Signal distribution via UTP cable
- Stand-alone operation possible with 30 built-in light programs
- Master/Slave for parallel operation of several devices

Logistique

- Comfortable addressing and setting via control panel with LC display
- RGB color mixture, dimmer and strobe function
- P-Con terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- Commandé via stand-alone; ArtNet; DMX
- Déjà préprogrammé pour %: LED PC-Control 512

OMNITRONIC Câble CAT-5 5 m noir

Câble de données ou câble réseau

- OEM
- Made in Germany

OMNITRONIC Câble CAT-5 1 m noir

Câble de données ou câble réseau

- OEM

MADRIX KEY entry

MADRIX KEY + MADRIX 5 license entry

- Includes 1x MADRIX KEY and 1x MADRIX 5 License entry
- MADRIX 5 is a powerful, easy-to-use, and award-winning LED lighting control software
- Allows you to realize all kinds of different LED projects and lighting designs
- A normal PC/laptop can be used for professional LED control
- Activates output for up to 8x 512 DMX channels (4,096 DMX channels, or 8 DMX universes, for example) and up to 16,384 DVI voxels (a resolution of 128 x 128 pixels, for example)
- The license is activated via a USB dongle and can be used flexibly on different computers as needed
- Can be upgraded to higher licenses (up to MADRIX 5 KEY maximum)
- Online activation is initially required one time
- Only one MADRIX 5 License is possible per MADRIX KEY
- Only one MADRIX 5 KEY can be connected to the software
- Supports many industry protocols and communication standards for direct connection to your LEDs and LED controllers: Art-Net (I, II, 3, 4) (Unicast & Broadcast), DMX512, Philips Color Kinetics KiNET (V1 / V2), Philips Hue, SPI (via MADRIX NEBULA), Streaming ACN (sACN / E1.31) (Unicast & Multicast), ColourSmart Link, Colorlight A8, Colorlight 5A, Colorlight T9, DVI (VGA, HDMI, and more), EuroLite T9
- Even more options are available via converters or bridging tools
- Allows mapping in 2D (pixel mapping) as well as real, spatial 3D (voxel mapping)
- The software generates unique effects, visuals, and animations live and in real time
- No additional content is required
- Already includes a multitude of stock effects that are fully customizable (in speed, color, shape, direction, size, movement, position, brightness, and many more)
- Analyzes incoming audio signals for Sound2Light and Music2Light in real time (WDM or ASIO)
- TRI effect category for interactive performances
- New lighting scenes can easily be created in seconds
- Supports media server features also: Conveniently load and play back images, pictures, logos, and videos as well as live video signal capturing, screen capturing, scrolling text (ticker), and more
- Supports audio playback for videos
- Variety of options to combine visuals and graphical elements (layers, mix modes, filters, etc.)
- Clean and simple user interface with 2 themes (dark and light)
- DJ-/VJ-like operation with 2 decks (A/B) and a crossfader
- 256 x 256 Storage Places to organize and store effects
- 3 real-time previews to show your visual effects in advance (incl. 2D/3D, zoom, rotation)
- 2 DVI outputs
- Controls up to 4 color channels per pixel/voxel (1-channel, 2-channel, RGB, RGBW fixtures, for example)
- Freely configurable Cue List for automated playback of a show (incl. time, date, duration, etc.)
- Supports Time Code (Art-Net, MIDI, SMPTE, and System Time)

- Input, interoperability, and remote control available through industry standards: Art-Net (I, II, 3, 4), Blackmagic Design (DeckLink, Intensity, and more), C1TP, DMX512, GamePort, MA-Net 1 / MA-Net 2, MADRIX I/O, MIDI, NewTek NDI (Send & Receive), Remote HTTP (Web Server), Spout (Send & Receive), Streaming ACN (sACN / E1.31)
- Even more options are available via converters or bridging tools
- Accompanying Fixture Editor including large fixture library
- Comfortable patching features (incl. Matrix Generator, graphical Patch Editor with background image support, DVI Patch, CSV Fixture List Import, Fixture List Export, and more)
- Includes various other tools and features (Art-Net Time Code Sender, DMX Fader Tool, DMX Watcher, MIDI Watcher, Touch Screen window, backup system, scripting, mapping, scaling, etc.)
- Supports various 3rd-party interfaces via aforementioned standards as well as MADRIX hardware interfaces (sold separately)
- Minimum system requirements: 2.0 GHz dual-core CPU, OpenGL 2.1 graphics card (NVIDIA recommended), 2 GB RAM, 1 GB free harddisk space, 1280 x 768 screen resolution, network card, sound card, USB 2.0 (optimal system specifications will often be higher)
- Supported operating systems: Microsoft Windows 7 | 8 | 8.1 | 10 (64 bit only)
- Package contents: Beautiful, high-quality box including 1x MADRIX KEY, 1x USB flash drive incl. MADRIX 5 Software, 1x lanyard, and 1x quick start guide
- Software and installation instructions available in English, German, Spanish, French, and Simplified Chinese
- All user manuals are provided digitally and available in English
- User manuals also available at help.madrix.com
- Made in Germany
- Free software demo mode and more information available at www.madrix.com

Données techniques:

Poids: 6,34 kg

EUROLITE LED Pixel Pole 50 cm

Alimentation électrique: 24 V CC

Puissance totale de raccordement: 2 W

Classe de protection: SK III

Branchement électrique: Alimentation électrique via RJ-45 (F) version encastrable

LED: 16 x SMD 5050 3in1 TCL RGB (mélange de couleurs homogène)

Commande: Accessoire; Fonction maître/esclave

Angle de départ: 180°

Angle de départ (1/2 pic): 180°

Image: 16 px
Distance entre les pixels 30 mm
%

Couleur du boîtier: Argenté

Connexions: Signal via 2 x RJ-45 (F) version encastrable

Dimension: Longueur : 50 cm
Profondeur : 3,2 cm
Hauteur : 3,2 cm

Poids: 110 g

Spécifications juridiques

Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle

EUROLITE LED PSU-4A Artnet/DMX

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	200 W
Type de protection:	IP20
Branchement électrique:	Alimentation électrique via P-Con (bleu), version encastrable Câble d'alimentation à prise contact de protection (inclus dans la livraison)
Canaux DMX:	8
Entrée DMX:	1 x XLR (M) 3 broches version encastrable
Sortie DMX:	1 x XLR (F) 3 broches version encastrable
Connexion au réseau:	2x RJ-45 (F) version encastrable
Commande:	Stand-alone; ArtNet; DMX
Préprogrammé dans:	LED PC-Control 512
Couleur du boîtier:	Noir
Dimension:	Largeur : 21,5 cm Profondeur : 28,5 cm Hauteur : 8,5 cm
Poids:	2,57 kg
Serial connection:	yes
Art-Net control:	4 x 160 pixels

OMNITRONIC Câble CAT-5 5 m noir

Conception du câble:	CAT5
Longueur du câble:	5 m
Raccord A:	1 x RJ-45 (M)
Raccord B:	1 x RJ-45 (M)
Utilisation de la marque:	OEM
Couleur:	Noir
Poids:	180 g

OMNITRONIC Câble CAT-5 1 m noir

Conception du câble:	CAT5
Longueur du câble:	1 m
Raccord A:	1 x RJ-45 (M)
Raccord B:	1 x RJ-45 (M)
Utilisation de la marque:	OEM
Couleur:	Noir
Poids:	50 g