



**L'article n'est plus disponible.**

---

**Caractéristiques:****OMNITRONIC UHF-201 Wireless Mic System 863.010MHz**

Wireless microphone system with UHF PLL technology

- Receiver unit and hand-held microphone with UHF PLL technology
- Operation in the low-interference UHF band
- Parallel operation of up to 4 sets is possible without any interference
- Volume control
- XLR and 6.3 mm output
- Jack cable included
- LEDs for power, carrier and audio signal
- Microphone with mute switch and color indication
- Matching pocket transmitter can be ordered separately
- License-free and approved in the EU
- Caractéristique directionnelle: Cardioïde
- UHF 863-865 MHz sans inscription et sans frais en Europe

**L'étendue des fournitures**

- 1 x microphone

**OMNITRONIC UHF-200 BP Bodypack 863.010MHz**

Émetteur de poche et micro cravate

- Pocket transmitter as UHF PLL system, matching receivers with the same carrier frequency
- Operation in the low-interference UHF band
- Incl. lavalier microphone
- Transmitting power 10 mW
- Sensitivity adjustable

---

**Logistique**

- Power LED
- Mute switch
- Operation via 2 x 1.5 V batteries, type AA
- License-free and approved in the EU
- Caractéristique directionnelle: Cardioïde
- UHF 863-865 MHz sans inscription et sans frais en Europe

## Données techniques:

---

Poids: 830 g

---

### OMNITRONIC UHF-201 Wireless Mic System 863.010MHz

|                                   |  |
|-----------------------------------|--|
| Type:                             | Ensemble complet sans fil  |
| Puissance totale de raccordement: | 10,00 W  |
| Type de micro:                    | Dynamique  |
| Caractéristique directionnelle:   | Cardioïde  |
| Plage de fréquence:               | 40 - 18000 Hz  |
| Bande de fréquences:              | UHF 863-865 MHz  |
| Sélection de la fréquence:        | Fréquence fixe   |
| Dimension:                        | Largeur : 21 cm<br>Profondeur : 4,5 cm<br>Hauteur : 15,5 cm              |
| Poids:                            | 720 g  |
| Microphone                        |  |
| Batterie:                         | 2 x Mignon (AA) (non incluse dans la livraison)                          |
| System:                           | Non-Diversity  |
| Carrier frequency:                | 863.010 MHz  |
| Coverage:                         | 50 m (with line-of-sight)  |
| RF power output:                  | 10 mW  |
| Modulation method:                | F3F  |
| S/N ratio:                        | >105 dB  |
| Selectivity:                      | >80 dB   |
| T.H.D.:                           | <0.5 % at 1 kHz  |
| Audio outputs:                    | 400 mV, 2.2 kohms (XLR, bal.)<br>200 mV, 2.2 kohms (6.3 mm jack, unbal.) |
| Power supply                      |  |
| Receiver:                         | 100-240 V AC, 50/60 Hz via supplied power unit                           |
| Dimensions, weight:               |  |
| Receiver:                         | 155 x 210 x 45 mm (W x D x H), 1 kg                                      |
| Microphone:                       | 50 x 265 mm (D x L), 280 g   |

### OMNITRONIC UHF-200 BP Bodypack 863.010MHz

Type: Émetteur de poche et microphone

---

|                                 |   |
|---------------------------------|---|
| Type de micro:                  | Condensateur  |
| Caractéristique directionnelle: | Cardioïde   |
| Batterie:                       | 2 x Mignon (AA) (non incluse dans la livraison)           |
| Plage de fréquence:             | 40 - 18000 Hz   |
| Bande de fréquences:            | UHF 863-865 MHz   |
| Sélection de la fréquence:      | Fréquence fixe  |
| Commutateur:                    | Commutateur marche/arrêt; Commutateur muet                |
| Dimension:                      | Largeur : 65 cm<br>Profondeur : 20 cm<br>Hauteur : 2,5 cm |
| Poids:                          | 120 g   |
| Carrier frequency:              | 863.010 MHz   |
| Coverage:                       | 50 m (with line-of-sight)                                 |
| RF power output:                | 10 mW   |
| Modulation method:              | F3F   |
| S/N ratio:                      | >105 dB   |
| Selectivity:                    | >80 dB  |
| T.H.D.:                         | <0.5 % at 1 kHz   |
| Connection:                     | 3.5 mm jack   |