



Caractéristiques:

EUROLITE LED PT-100 DMX Pixel Tube

DMX controlled pixel tube

- Tube with 144 LEDs: 48 x red, 48 x green, 48 x blue
- Subdivided into 16 pixels (illumination units à 9 LEDs) which can be controlled individually by DMX
- Can be cascaded as desired in order to build-up large effect areas
- Operable in stand-alone mode or via DMX interface
- DMX-512-connection via 5-pin XLR socket and plug
- Sound-control via built-in microphone
- Master/Slave for parallel operation of several devices
- Comfortable addressing and setting via control panel with LED display and four operating buttons
- Functions: static colors, automatic color change, seven internal programs with variable speed, dimmer settings via DMX
- Adjustable white balance
- Plastic housing with brackets for hanging as well as standing installation indoors
- IEC terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- 144 LED 5 mm 3in1 TCL RGB (mélange de couleurs homogène)
- L'appareil est refroidi par refroidissement par convection passive
- Commandé via stand-alone; DMX; commande de la musique via microphone
- Fixtures disponibles pour LED PC-Control 512

MADRIX NEO - Interface USB-DMX512

Interface USB/DMX Madrix pour un univers DMX, XLR

Logistique

- MADRIX NEO is a reliable, easy-to-use, and high-quality DMX512 USB hardware interface including MADRIX software for LED control and MADRIX 3 software license
- The interface can be used for DMX input or DMX output to connect DMX512 devices to your computer
- The MADRIX software license for 512 DMX channels per device is already included and automatically activated when connected to MADRIX
- If you want to use DMX-IN, please use a 5-pin XLR male to 5-pin XLR male gender changer
- The MADRIX 3 Software license for 512 DMX channels per device is already included and automatically activated when connected to MADRIX
- Full USB 2.0 support, Power over USB, Hot Swapping, and Plug & Play
- Multiple devices can be used together without problems for larger projects
- Rugged metal housing with eye-catching design
- MADRIX is a powerful, easy-to-use, and award-winning LED lighting control software
- Allows you to realize all kinds of different LED projects and lighting designs
- A normal PC/laptop can be used for professional LED control
- Allows mapping in 2D (pixel mapping) as well as real, spatial 3D (voxel mapping)
- The software generates unique effects, visuals, and animations live and in real time
- No additional content is required
- Already includes a multitude of stock effects that are fully customizable (in speed, color, shape, direction, size, movement, position, brightness etc.)
- Analyzes incoming audio signals Sound2Light and Music2Light in real time
- New lighting scenes can easily be created in seconds
- Variety of options to combine visuals and graphical elements (layers, mix modes, filters, etc.)
- 256 x 256 Storage Places to organize and store effects
- DJ-like operation with 2 decks (Left/Right) and a crossfader
- 3 real-time previews to show your visual effects in advance (incl. 2D/3D, zoom, rotation)
- Controls up to 4 color channels per pixel/voxel (e.g. 1-channel, 2-channel, RGB, RGBW fixtures)
- Freely configurable Cue List for automated playback of a show (incl. time, date, duration, etc.)
- Supports Time Code from Art-Net, MIDI, SMPTE, and system time
- Remote control available via DMX-IN, Art-Net Remote, MIDI-IN, HTTP (internet browser), CIP
- Incl. Fixture Editor with large fixture library
- Includes various other tools and features (DMX Fader Tool, DMX Watcher, Matrix Generator, Patch Editor, Touch Screen window, backup system, scripting, mapping, scaling, etc.)
- MADRIX minimum system requirements: 2.0 GHz dual-core CPU, OpenGL 2.0 graphics card (NVIDIA recommended), 2 GB RAM, 1 GB free harddisk space, 1280 x 768 screen resolution, network card, sound card, USB 2.0
- Installation instructions and software available in English, Spanish, French, and Simplified Chinese
- User manuals also available at help.madrix.com
- More information available at www.madrix.com
- Peut recevoir et traiter jusqu'à 512 canaux DMX
- Peut envoyer jusqu'à 512 canaux DMX
- Commandé via DMX via USB
- Connexion enfichable NEUTRIK intégrée
- Made in Germany

Données techniques:

Poids: 20,24 kg

EUROLITE LED PT-100 DMX Pixel Tube

Alimentation électrique: 100-240 V CA, 50/60 Hz

Puissance totale de raccordement: 17 W

Type de protection: IP20

Branchement électrique:	Alimentation électrique via appareils froids (M) version encastrable câble d'alimentation à prise contact de protection (inclus dans la livraison)
	Tramite
Sortie de courant:	1 x appareils froids (F) version encastrable
Type de LED:	144 x 5 mm 3in1 TCL RGB (mélange de couleurs homogène)
Canaux DMX:	48
Entrée DMX:	1 x XLR (M) 5 broches version encastrée
Sortie DMX:	1 x XLR (F) 5 broches version encastrée
Refroidissement:	Refroidissement par convection passive
Commande:	Stand-alone; DMX; commande de la musique via microphone
Fixtures disponibles pour:	LED PC-Control 512
Angle de départ (1/2 pic):	120°
Couleur du boîtier:	Noir
Dimension:	Longueur : 100 cm Profondeur : 5,2 cm Hauteur : 15,3 cm
Poids:	2,00 kg
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle

MADRIX NEO - Interface USB-DMX512

Alimentation électrique:	5V CC 500 mA
Branchement électrique:	Alimentation électrique via USB, type B câble d'alimentation pour raccordement au réseau USB A (inclus dans la livraison)
	Tramite
Canaux DMX:	Entrée 512 Sortie 512
Sortie DMX:	1 x XLR (F) 5 broches version encastrée
Commande:	DMX via USB
Port USB:	USB 2.0, type B
Utilisation de la marque:	Connexion enfichable NEUTRIK intégrée
Dimension:	Largeur : 7,8 cm Profondeur : 5,9 cm Hauteur : 3,5 cm
Poids:	0,24 kg

Contenu de la livraison:

10 x EUROLITE LED PT-100 DMX Pixel Tube

1 x Effet lumineux
1 x Mode d'emploi
1 x Câble secteur/câble d'alimentation

1 x MADRIX NEO - Interface USB-DMX512

1 x Appareil

1 x Mode d'emploi
1 x CD
1 x Câble USB