

EUROLITE SBP-3240K Power Distributor

Distributeur de courant de chantier 1 x 32 A, 2 x 16 A, 4 x 230 V

Réf. : 30245541

GTIN: 4026397462371



L'article n'est plus disponible.

Caractéristiques:

- Plastic box with 4 safety sockets
- 1 x 32 A CEE input with 2 meter cable
- 1 x 32 A CEE output, 5-pin
- 2 x 16 A CEE outputs, 5-pin
- The entire distributor is secured via 30 mA Residual Current Device (RCD)

Logistique

EAN / GTIN: 4026397462371

Poids: 5,55 kg

Longueur: 0.47 m

Largeur: 0.40 m

Hauteur: 0.12 m

Données techniques:

Branchement électrique:	Fixe Câble d'alimentation et CEE 32 A 5 broches
Sortie de courant:	4 x Contact de protection (F), version encastrable avec couvercle rabattable sécurisé 2 x CEE 16 A 5 broches (F) version encastrable sécurisé 1 x CEE 32 A 5 broches (F) version encastrable sécurisé
Dimension:	Largeur : 30 cm Profondeur : 44,5 cm Hauteur : 11 cm
Poids:	5,20 kg
Power supply:	380-400 V AC, 50 Hz
Max. power output:	22080 W

Max. total current:	96 A
Max. output/phase (32 A CEE):	7360 W
Max. current/phase (32 A CEE):	32 A
Max. output/phase (16 A CEE):	3680 W
Max. current/phase (16 A CEE):	16 A
Max. output/channel (safety socket):	3680 W
Max. current/channel (safety socket):	16 A
RF:	0.8
Dimensions (L x W x H):	445 x 300 x 110 mm