

EUROLITE LED ML-56 COB 5600K 50W 60° bk

LED daylight spot in proven Multi Lens design

Réf. : 41604000

GTIN: 4026397440065



L'article n'est plus disponible.

Caractéristiques:

- Equipped with one powerful 50 W COB LED
- Functions: dimmer, strobe effect, Master/Slave operation
- Operable in stand-alone mode or via DMX
- 1 or 3 DMX channels selectable for numerous applications
- Beam angle approximately 60°
- Different dimmer curves and dimmer speed adjustable
- 5600 K color temperature
- Mounting bracket for installations on a stand or a crossbeam
- Locking possibility at the mounting bracket
- Comfortable addressing and setting via Control Board with LCD display and four operating buttons
- Ready for connection with power cord and safety plug
- With color filter frame
- Optional barndoors available
- Ideal for theatres, large stages as pre-stage spot and mobile use
- Available in silver or black
- 1 LED puissante 50 W
- Commandé via stand-alone
- Déjà préprogrammé pour %: LED PC-Control 512

Logistique

EAN / GTIN: 4026397440065

Poids: 4,40 kg

Longueur: 0.28 m

Largeur: 0.27 m

Hauteur: 0.38 m

Données techniques:

Alimentation électrique: 230 V AC, 50 Hz

Puissance totale de raccordement: 85,00 W

| | |
|----------------------------|--|
| Type de protection: | IP20 |
| Type de lampe: | Lampe LED |
| LED: | 1 x 50 W |
| Commande: | Stand-alone |
| Préprogrammé dans: | LED PC-Control 512 |
| Angle de départ (1/2 pic): | 60° |
| Couleur du boîtier: | Noir |
| Dimension: | Largeur : 30 cm Profondeur : 30 cm Hauteur : 24 cm |
| Poids: | 3,90 kg |
| DMX channels: | 1/3 |
| DMX connection: | 3-pin XLR |
| LED type: | Array 50 W |
| LED number: | 1 |
| Color temperature: | 5600 K |
| Beam angle: | 60° |
| Dimensions (L x W x H): | 240 x 300 x 300 mm |
| Spécifications juridiques | |
| Produit spécial: | Non destiné à l'éclairage de la pièce dans les ménages |
| Utilisation: | Éclairage pour effets de spectacle |