

## EUROLITE Audience Blinder 4x50W LED COB 3200K

PRO audience blinder with 4 x 50 W COB LED

Réf. : 41606125

GTIN: 4026397467062



**L'article n'est plus disponible.**

### Caractéristiques:

- 3200 K color temperature
- 1, 2, 4, 6 or 7 DMX channels selectable for various applications
- Each LED can be controlled individually
- Functions: built-in programs and strobe effect with variable speed, dimmer, Master/Slave
- Different dimmer curves and dimmer speed adjustable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- For use on stages, catwalks, crossbeam systems, or decoration
- Swivelable lamp rows
- Rugged housing and an appealing design
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Locking possibility at the mounting bracket
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 devices the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- Déjà préprogrammé pour %: Light´J; Light Captain

### Logistique

EAN / GTIN: 4026397467062

Poids: 11,00 kg

Longueur: 0.53 m

Largeur: 0.51 m

Hauteur: 0.26 m

### Données techniques:

Alimentation électrique: 230 V AC, 50 Hz

Puissance totale de raccordement: 250 W

Type de protection: IP20

Température de couleur: 3200K

Fréquence du flash:	1 - 20 Hz
Canaux DMX:	2; 1
Préprogrammé dans:	Light´J; Light Captain
Angle de départ (1/2 pic):	60°
Dimension:	Largeur : 40 cm Profondeur : 49,5 cm Hauteur : 17,5 cm
Poids:	9,10 kg
DMX channels:	1/2/4/6/7
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	20 Hz
LED number:	4
LED type:	Array 50 W, white
Color temperature:	3200 K
Beam angle:	60°
Dimensions (L x W x H):	175 x 400 x 415 mm
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle