


EUROLITE Audience Blinder 4xPAR-36 QCL LED bk

LED Audience Blinder with PAR-36 Blinder housing with RGBW LEDs (4in1)

Réf. : 42103479

GTIN: 4026397443035



L'article n'est plus disponible.

Caractéristiques:

- Equipped with 24 x 8 W QCLs (quadcolor LEDs) distributed in 4 segments
- Each segment can be controlled individually via DMX
- Sound-control via built-in microphone; sensitivity adjustable
- Functions: Static colors, RGBW color mixture, internal programs, dimmer and strobe settings via DMX, Master/Slave
- 4, 6 or 19 DMX channels selectable for numerous applications
- DMX-controlled operation or stand-alone operation with Master/Slave function
- For use on stages, catwalks, crossbeam systems, or decoration
- Swivelable lamp rows
- Rugged housing and an appealing design
- Comfortable addressing and setting via control panel with LCD display and four operating buttons
- Locking possibility at the mounting bracket
- DMX control via every standard DMX controller
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- Commandé via Commande de la musique via Microphone

Logistique

EAN / GTIN: 4026397443035

Poids: 14,05 kg

Longueur: 0.65 m

Largeur: 0.50 m

Hauteur: 0.27 m

Données techniques:

Alimentation électrique: 230 V AC, 50 Hz

Puissance totale de raccordement: 220 W

Type de protection: IP20

Fréquence du flash:	1 - 20 Hz
Canaux DMX:	4
Commande:	Commande de la musique via Microphone
Angle de départ (1/2 pic):	19°
Dimension:	Largeur : 44,5 cm Profondeur : 19 cm Hauteur : 56,5 cm
Poids:	11,95 kg
DMX channels:	4/6/19
DMX connection:	3-pin XLR
Flash-rate:	20 Hz
Sound-control:	via built-in microphone
LED type:	8 W QCL
LED number:	24
Beam angle:	19°
Dimensions (L x W x H):	190 x 445 x 565 mm
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle