

000



## L'article n'est plus disponible.

### Description:

#### EUROLITE quick links

The EUROLITE quick links comply with the current regulation of the German professional insurance association as summed up in BGI 810-3:2007-03 Loads above persons. The quick links are constructed in accordance with the German standard DIN 56927:2009-03.

The quick links are manufactured by a renowned German supplier and are tested by the LGA, an independent and accredited testing institute. The breaking load testified by the LGA is documented in the test report according to DIN EN 10204 required by the German professional insurance association.

Clearly, every user can secure loads above persons with these quick links in all areas where the BGV C1 is required.

### Logistique

EAN / GTIN: 4026397381665

Poids: 0,03 kg

Longueur: 0,06 m

Largeur: 0,03 m

Hauteur: 0,01 m

### Caractéristiques:

- Complies with DIN 56927:2009-03
- Nominal size: 6 mm
- Form A (short)
- Galvanized
- Identification number: 200
- Stamp: DIN 56927 A 200
- Test report according to DIN EN 10204 as download
- Correspond DIN 56927:2009-03
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

## Données techniques:

---

Charge maximale WLL (5 fois):	400 kg
Norme:	DIN 56927:2009-03,
Dimension:	Largeur : 5,80 cm Profondeur : 2,70 cm
Maximum load WLL (5-fold):	400 kg
Maximum load BGV C1 (10-fold):	200 kg
Identification:	DIN 56926-A-200
Temperature range:	-40° C to +100° C
Diameter:	6 mm
Form:	A - small
Spanner opening:	7.5 mm
Dimensions:	58 x 27 mm
Weight:	30 g

---