

EUROLITE LED IP Strip 300 5m 3000K 12V

Ruban de LED souple pour l'intérieur et l'extérieur

Réf. : 50530185

GTIN: 4026397426809



L'article n'est plus disponible.

Description:

With its numerous IP LED strips, Eurolite offers light on tape for outdoor use. Eurolite presents different stripes fulfilling the IP68 standard.

The flexible LED strips have a length of 5 meters. Unichrome versions - red, blue, green, yellow, cool white, warm white - are complimented by two RGB versions. The single colors can be ordered either with a wide span (150 LEDs) or with a short span (300 LEDs) between the LEDs. The RGB versions are available in 12 V or 24 operation - LED quantities are always 150. An optional LED controller controls the brightness and the speed of the RGB LEDs or provides automatic run of the built-in color programs.

Supplied on a plastic reel, the LED stripes feature a self adhesive rear side for simple installation. Color and form can be used as desired as the strips are very flexible and adaptable to really every venue.

Caractéristiques:

- Flexible LED strip for decorative lighting
- Perfect for indirect lighting, custom-made versions for fair or shop applications as well as all kinds of background lighting
- For indoor and outdoor use (IP44)
- Can be cut into segments of variable size (groups of 3 LEDs)
- Self-adhesive rear side
- Supplied on a plastic reel
- Matching control units and power units optionally available
- Different versions available
- Convient à une utilisation en extérieur IP44

Logistique

EAN / GTIN: 4026397426809

Poids: 0,20 kg

Longueur: 0.18 m

Largeur: 0.18 m

Hauteur: 0.01 m

Données techniques:

Puissance totale de raccordement:	20 W
Type de protection:	IP44
Installation/fixation:	Autocollant
Lampes/mètre:	60 Pièce
Puissance/mètre:	4,8 W
Lampes/tuyau:	300 Pièce
Distance entre les lampes:	16 mm
Marquage de la découpe:	5 cm
Couleur du boîtier:	Blanc
Dimension:	Longueur : 5 m
Poids:	180 g
Watts per meter/total:	4.8 W/max. 20 W
Protection grade:	IP44
LED type:	SMD 3528
LED number:	300
Color temperature:	3300 K
Cutting mark:	every 50 mm
Dimensions:	Ø 8 mm x 5000 mm