

EUROLITE TMH XB-230 Moving-Head Beam

High performance beam for 230 W discharge lamp

Réf. : 51786820

GTIN: 4026397555974



L'article n'est plus disponible.

Caractéristiques:

- Very narrow beam angle with 3°
- With electronic ballast
- Color wheel with 14 different dichroic color filters plus white
- Switchable color change (mode 1: only full colors, mode 2: half colors)
- Rainbow effect with adjustable speed
- 8-facet prism
- Frost-filter
- Gobo wheel with 17 static gobos plus open
- With gobo shake function
- Motorized focus
- Strobe effect with adjustable speed
- Random strobe effect
- Dimmer
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- Switch-mode power supply for operation between 100 and 240 volts
- Control board with graphic LC display and encoder for adjusting the DMX-starting address, PAN/TILT reverse, reset, lamp on/off, operating hours
- DMX-controlled operation or stand-alone operation with master/slave function
- For OSD 7 Reflector 230 W discharge lamp
- Power connection via Neutrik PowerCon socket and included power cable
- DMX-control via every standard DMX-controller
- Gobos
- Effet beam
- L'appareil est refroidi par ventilateur
- Commandé via DMX; stand-alone

Logistique

EAN / GTIN: 4026397555974

Poids: 21,60 kg

Longueur: 0.47 m

Largeur: 0.43 m

Hauteur: 0.62 m

- Déjà préprogrammé pour %: LED PC-Control 512
- Avec un Angle de départ de 3°

Données techniques:

| | |
|-----------------------------------|--|
| Alimentation électrique: | 100-240 V CA, 50/60 Hz |
| Puissance totale de raccordement: | 300 W |
| Type de protection: | IP20 |
| Type de lampe: | Lampe à décharge |
| Équipement: | Gobos |
| Refroidissement: | Ventilateur |
| Commande: | DMX; stand-alone |
| Préprogrammé dans: | LED PC-Control 512 |
| Angle de départ: | 3° |
| Angle de départ (1/2 pic): | 3° |
| Couleur du boîtier: | Noir |
| Dimension: | Largeur : 39,5 cm Profondeur : 32 cm Hauteur : 51 cm |
| Poids: | 19,14 kg |
| DMX channels: | 16 |
| DMX connection: | 5-pin and 3-pin XLR |
| Flash-rate: | 18 Hz |
| Color-wheel: | 14 dichroic filters plus open |
| Static gobo-wheel: | 17 gobos and open |
| Maximum PAN-movement: | 540° |
| Maximum TILT-movement: | 250° |
| Beam angle: | 3° |
| Dimensions (L x W x H): | 395 x 320 x 510 mm |
| Spécifications juridiques | |
| Produit spécial: | Non destiné à l'éclairage de la pièce dans les ménages |
| Utilisation: | Éclairage pour effets de spectacle |