

FUTURELIGHT WL-250 MK2 Wall Light

Projecteur d'extérieur 250 W

Réf. : 51833577

GTIN: 4026397214086



L'article n'est plus disponible.

Caractéristiques:

- Static spot with CMY color mixing
- Motorized shutter
- For architectural lighting
- Fully convection cooled, no fans
- High-precision aluminum die-cast housing
- Suitable for external use (IP33)
- Elliptical reflector for maximum light output
- Pre-programmed variable/random CMY color-combinations
- Can also be operated without external controller (stand-alone mode and master/slave)
- For MSD/HSD 250, MSD 250/2 or MSD/HSD 200 lamp
- DMX control via every standard DMX controller

Logistique

EAN / GTIN: 4026397214086

Poids: 19,00 kg

Longueur: 0.45 m

Largeur: 0.30 m

Hauteur: 0.66 m

Données techniques:

Alimentation électrique: 230 V AC, 50 Hz

Puissance totale de raccordement: 600 W

Type de protection: IP33

Canaux DMX: 4

Angle de départ (1/2 pic): 21°

Dimension: Largeur : 36 cm
Profondeur : 22,5 cm
Hauteur : 59,5 cm

Poids:	17,80 kg
Protection grade:	IP33
Beam angle:	21°
DMX channels:	4
DMX connection:	3-pin XLR
Dimensions (L x W x H):	225 x 360 x 595 mm
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle