

## FUTURELIGHT RDM Director Touch Screen

RDM controller with TFT touchscreen

Réf. : 51834850

GTIN: 4026397451481



## L'article n'est plus disponible.

### Description:

RDM stands for "Remote Device Management" and makes remote control of devices connected to the DMX-bus possible. ANSI E1.20-2006 by ESTA specifies the RDM standard as an extension of the DMX512 protocol.

Manual settings like adjusting the DMX starting address are no longer needed. This is especially useful when the device is installed in a remote area.

RDM is integrated in the DMX-protocol without influencing the connections. The RDM-data is transmitted via the standard XLR-line - new DMX-cables are not necessary. RDM ready and conventional DMX devices can be operated in one DMX line. The RDM protocol sends own packages in the DMX512 data feed and does not influence conventional devices.

If DMX splitters are used and RDM control is to be used, these splitters must support RDM.

### Caractéristiques:

- RDM controller for monitoring and remote control of DMX fixtures compliant with RDM (Remote Device Management)
- Quick analysis and configuration of fixture parameters, i.e. DMX start address, DMX mode, lamp hour count, fixture status
- TFT touchscreen for menu settings
- Various basic DMX control features integrated
- 1 DMX universe
- USB port for firmware updates
- 3-pin XLR connectors
- Power supply via included PSU
- Peut envoyer jusqu'à 512 canaux DMX

### Logistique

EAN / GTIN: 4026397451481

Poids: 1,42 kg

Longueur: 0.33 m

Largeur: 0.15 m

Hauteur: 0.07 m

- Made in Europe

## Données techniques:

---

Alimentation électrique:	100-240 V CA, 50/60 Hz 12 V CC 1 A
Puissance totale de raccordement:	12 W
Branchement électrique:	Alimentation électrique via Connecteur fileté (M) 4 broches version encastrable Câble d'alimentation et bloc d'alimentation (inclus dans la livraison)
Canaux DMX:	Sortie 512
Entrée DMX:	1 x XLR (M) 3 broches version encastrable
Sortie DMX:	1 x XLR (F) 3 broches version encastrable
Port USB:	USB 2.0, Typ B
Profondeur de pose:	60 mm
Dimension:	Largeur : 23 cm Profondeur : 13,3 cm Hauteur : 6 cm
Poids:	1,30 kg

---