

FUTURELIGHT PHS-300E PRO-Head Spot

Multifunctional Moving Head

Réf. : 51838240

GTIN: 4026397318944



L'article n'est plus disponible.

Caractéristiques:

- With electronic ballast
- Lower heat emission with closed shutter due to reduced lamp power, resulting in longer lifetime of the lamp
- Color-wheel with 5 different, dichroic color filters and white and additionally with CTO and CTB correction-filters and UV-filter
- CMY color mixing for indefinite color variations
- Switchable color change (mode 1: only full colors, mode 2: color-change at every position)
- Rainbow effect with adjustable speed in both directions
- Slot-in system for exchanging gobos and color-filters without tools
- Gobo-wheel 1 with 6 rotating gobos plus open
- All gobos can be interchanged
- Gobo-wheel 2 with 7 static metal gobos plus open
- With gobo-shake function
- Effect-wheel with rotating 3-facet prism, 3D prism and frost-filter
- Macro-function for rotating gobos/rotating prism combinations
- Motorized focus
- Mechanic dimmer
- Steplessly adjustable iris
- LCD-display
- Strobe effect with 1-13 flashes per second via shutter
- Random strobe effect
- Exact positioning via 16 bit Pan/Tilt movement resolution
- PAN-angle switchable between 630° and 540°
- Control board with LCD-display and foil-keyboard for adjusting the DMX-starting address, Pan/Tilt-Reverse, Program, Reset, lamp on/off, operating hours
- DMX-controlled operation or stand-alone operation with Master/Slave function

Logistique

EAN / GTIN: 4026397318944

Poids: 30,70 kg

Longueur: 0.71 m

Largeur: 0.46 m

Hauteur: 0.55 m

- 56 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 7 built-in programs can be called up via DMX controller
- Sound-controlled via built-in microphone
- For MSR 300SA/SE GOLD FASTFIT lamp
- DMX control via every standard DMX controller

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	500,00 W
DMX channels:	21
DMX connection:	3-pin XLR
Beam angle:	21°
Flash-rate:	13 Hz
Color-system:	CMY color-mixture
Color-wheel:	5 dichroic plus white, CTO and CTB correction-filters, UV-filter
Rotating gobo-wheel:	6 gobos and open
Static gobo-wheel:	7 gobos and open
Outside diameter of the gobos:	27 mm
Image diameter of the gobos:	23 mm
Maximum PAN-movement 630°:	in 3.5 s
Maximum TILT-movement 265°:	in 2.5 s
Length of base (including handles):	350 mm
Width of yoke:	420 mm
Height (head horizontal):	510 mm
Weight:	26.5 kg
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle