

FUTURELIGHT PHW-575 PRO-Head WASH

Multifunctional Washlight

Réf. : 51838720

GTIN: 4026397316223



L'article n'est plus disponible.

Caractéristiques:

- Color-wheel with 5 different, dichroic color filters and white and additionally with UV-filter, correction-filters 3200 K and 5,600 K
- Switchable color change (mode 1: only full colors, mode 2: color-change at every position)
- Slot-in system for exchanging color filters without tools
- Colored LCD display
- Rainbow effect with adjustable speed in both directions
- CMY color mixing for indefinite color variations
- Macro-function for combinations between CMY color mixing and color-wheel
- Strobe effect with 1-13 flashes per second via shutter
- Random strobe effect
- Control board with LCD display and foil-keyboard for adjusting the DMX-starting address, Pan/Tilt reverse, Program, Reset, lamp on/off, operating hours
- Remotely switching of the lamp
- Built-in demo sequence
- Preprogrammed variable/random strobe and dimmer pulse effects
- Black-out while Head moving or CMY/color/beam shaping changing
- Remotely controllable speed of PAN /TILT movement for easy programming
- Remote reset function
- Motorized zoom
- Lightbeam with 13°-50° radiation angle
- Mechanic dimmer
- Exact positioning via 16 bit Pan/Tilt movement resolution
- PAN-angle switchable between 630° and 540°
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 56 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually

Logistique

EAN / GTIN: 4026397316223

Poids: 39,40 kg

Longueur: 0.72 m

Largeur: 0.46 m

Hauteur: 0.55 m

Article encombrant

- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 7 built-in programs can be called up via DMX controller
- Sound-controlled via built-in microphone
- For MSR 575SA/2 DE GOLD lamp
- DMX control via every standard DMX controller

Données techniques:

| | |
|-------------------------------------|--|
| Alimentation électrique: | 230 V AC, 50 Hz |
| Puissance totale de raccordement: | 850,00 W |
| DMX channels: | 15 |
| DMX connection: | 5-pin and 3-pin XLR |
| Flash-rate: | 13 Hz |
| Color-system: | CMY color-mixture |
| Color-wheel: | 5 dichroic + white, UV-filter, 2 correction filters |
| Maximum PAN-movement 630°: | in 3.5 s |
| Maximum TILT-movement 265°: | in 2.5 s |
| Length of base (including handles): | 470 mm |
| Width of yoke: | 350 mm |
| Height (head horizontal): | 520 mm |
| Weight: | 34 kg |
| Spécifications juridiques | |
| Produit spécial: | Non destiné à l'éclairage de la pièce dans les ménages |
| Utilisation: | Éclairage pour effets de spectacle |