

## FUTURELIGHT PSC-1200 MK2 PRO-Scan

The high-power scanner

Réf. : 51840006

GTIN: 4026397193428



## L'article n'est plus disponible.

### Caractéristiques:

- DMX-controlled operation or stand-alone operation with Master/Slave function
- 48 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the control board or via an external controller and loaded into the memory
- 8 built-in programs can be called up via DMX controller
- Sound-controlled via built-in microphone
- Color wheel 1 with 8 different, dichroic color filters and white
- Color wheel 2 with 5 different, dichroic color filters and white and additionally with correction filters 3200 K and 5,600 K and UV filter
- Switchable color change (mode 1: only full colors, mode 2: color change at every position)
- Rainbow effect with adjustable speed in both directions
- Gobo wheel 1 with 4 rotating gobos plus open
- All gobos can be interchanged
- Gobo wheel 2 with 5 static metal gobos plus open
- With gobo shake function
- Effect-wheel with rotating 3-facet prism, 5-facet prism, 7-facet prism, 9-facet prism and 3D prism
- Stepless frost filter
- The prisms rotate in both directions and at different speeds, prism index function
- Macro function for rotating gobos/rotating prism combinations
- Motorized multistep zoom with four different apertures
- Motorized focus
- Steplessly adjustable iris
- Strobe effect with 1-13 flashes per second via shutter
- Mechanic dimmer
- Exact positioning via 16 bit Pan/Tilt movement resolution

### Logistique

EAN / GTIN: 4026397193428

Poids: 50,60 kg

Longueur: 1.16 m

Largeur: 0.46 m

Hauteur: 0.38 m

Article encombrant

- Control board with 4-digit display and foil keyboard for adjusting the DMX starting address, Pan/Tilt Reverse, Program, Reset, lamp on/off, operating hours
- For extremely bright 1200 W HMI lamp
- DMX control via every standard DMX controller

## Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	1725,00 W
Dimension:	Largeur : 1,06 m Profondeur : 41 cm Hauteur : 24 cm
DMX channels:	19
DMX connection:	3-pin XLR
Beam angle:	14/20/27/33°
Flash-rate:	13 Hz
Color-wheel 1:	8 dichroic filters and open
Color-wheel 2:	5 dichroic filters, 2 correction filters, UV-filter and open
Static gobo-wheel:	5 gobos and open
Rotating gobo-wheel:	4 gobos and open
Gobo-size:	Rosco "D" (D=53.3 mm)
Dimensions (L x W x H):	1060 x 410 x 240 mm
Weight:	48 kg
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle