

## FUTURELIGHT Stage Pixel Bar 10

Bar with narrow beam 10 x 15 W RGBW LED and frost plate

Réf. : 51841359

GTIN: 4026397561098



### Caractéristiques:

- Equipped with 10 high-power 4in1 LEDs in the colors red, green, blue and white
- Particularly bright illuminating power of the LEDs
- Collimator lenses for homogeneous beams with 4° beam angle
- Removable frost filter
- 4, 6, 8, 40 or 44 DMX channels selectable
- Each LED can be controlled individually
- Quick and easy control via Art-Net
- For use via appropriate lighting control software supporting Art-Net
- Programmable color change speed, strobe effect and dimmer
- Dimmer speed (step response) adjustable
- Strobe effect with 1-18 flashes per second
- RGBW color mixing
- Static colors
- Internal programs
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Manual, sound, DMX- or ArtNet-controlled operation
- Sound-control via built-in microphone; adjustable sensitivity
- For large stage backgrounds in public places, main halls and lounges
- Hanging as well as standing installation possible
- Locking possibility at the mounting bracket
- Addressing via control panel with LCD screen and four operating buttons
- EtherCon input and output
- Switch-mode power supply for operation between 100 and 240 volts
- Power connection via Neutrik PowerCon jack and included power cable with safety plug
- Feed-through output allows to power up to 8 devices
- DMX control via any standard DMX controller

### Logistique

EAN / GTIN: 4026397561098

Poids: 11,60 kg

Longueur: 0.97 m

Largeur: 0.24 m

Hauteur: 0.27 m

- 10 LED 15 W high-power 4in1 RGBW (mélange de couleurs homogène)
- Effet stroboscope
- Commandé via Art-Net; stand-alone; DMX; commande de la musique via microphone; RDM
- Fixtures disponibles pour Light´J; LED PC-Control 512; EASY SHOW 1
- Exempt de scintillements
- Avec un Angle de départ de 4°

## Données techniques:

|                                   |   |
|-----------------------------------|---|
| Alimentation électrique:          | 100-240 V CA, 50/60 Hz  |
| Puissance totale de raccordement: | 170 W   |
| Branchement électrique:           | Alimentation électrique via PowerCON (bleu),<br>version encastrable câble d'alimentation à prise<br>contact de protection (inclus dans la livraison)<br><br>Tramite |
| Sortie de courant:                | 1 x PowerCON (gris), version encastrable  |
| Type de lampe:                    | Lampe LED   |
| Type de LED:                      | 10 x 15 W high-power 4in1 RGBW (mélange de<br>couleurs homogène)  |
| Fréquence du flash:               | 0 - 18 Hz   |
| Canaux DMX:                       | 4; 6; 8; 40; 44   |
| Commande:                         | Art-Net; stand-alone; DMX; commande de la<br>musique via microphone; RDM  |
| Fixtures disponibles pour:        | Light´J; LED PC-Control 512; EASY SHOW 1  |
| Projection:                       | Exempt de scintillements  |
| Angle de départ (1/2 pic):        | 4°  |
| Angle de départ (1/10 pic):       | 7°  |
| Couleur du boîtier:               | Noir  |
| Dimension:                        | Longueur : 88 cm<br>Profondeur : 15,9 cm<br>Hauteur : 17,8 cm   |
| Poids:                            | 9,70 kg   |
| Protocol:                         | Art-Net 3   |
| Signal port:                      | 2 x RJ45 (EtherCon)   |
| DMX connection:                   | 5-pin and 3-pin XLR   |
| Produit spécial:                  | Non destiné à l'éclairage de la pièce dans les<br>ménages   |
| Utilisation:                      | Éclairage pour effets de spectacle  |

## Contenu de la livraison: