

## FUTURELIGHT LB-648 LED Bar SMD 5050

PRO TCL bar with 110° beam angle

Réf. : 51841373

GTIN: 4026397474701



**L'article n'est plus disponible.**

### Caractéristiques:

- Equipped with 648 tricolor LEDs (81 LEDs x 8 segments)
- 8 LED segments independently controllable
- 3, 5, 7 or 24 DMX channels selectable for numerous applications
- Mounting bracket for installation on a truss system included
- Functions: static colors, RGB color change, internal programs, dimmer, Master/Slave
- Programmable color change speed
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Strobe effect with 1-30 flashes per second
- Sound-controlled via built-in microphone
- Microphone-sensitivity adjustable via rotary-control
- Comfortable addressing and setting via Control Board with LED display and four operating buttons with 14 segment display
- Feed-through output allows to power another device
- After every 6 devices the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller

### Logistique

EAN / GTIN: 4026397474701

Poids: 6,60 kg

Longueur: 0.86 m

Largeur: 0.20 m

Hauteur: 0.23 m

### Données techniques:

Alimentation électrique: 100-240 V CA, 50/60 Hz

Puissance totale de raccordement: 150,00 W

Dimension:  
Largeur : 80,3 cm  
Profondeur : 12,1 cm  
Hauteur : 17,8 cm

Poids:	5,50 kg
DMX channels:	3/5/7/24
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	1-30 Hz
Sound-control:	via built-in microphone
Beam angle:	110°
LED number:	648
LED type:	TCL, SMD 5050
Dimensions (W x D x H):	803 x 121 x 178 mm
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle