

FUTURELIGHT OFL-72 W/A IP65

Versatile LED outdoor daylight floodlight

Réf. : 51841382

GTIN: 4026397396034



L'article n'est plus disponible.

Caractéristiques:

- 2 or 5 DMX channels selectable for numerous applications
- Equipped with 72 x 1 W LEDs: 48 x white, 24 x amber
- Switch-mode power supply
- Automatic power supply adaption between 120 and 240 Volts without power selector
- For architectural lighting or large stage backgrounds
- Suitable for external use (IP65)
- Compact, matt grey housing
- Convection cooling via cooling ribs
- Programmable color temperature and strobe effect
- DMX-controlled operation or stand-alone operation
- Strobe effect with 1-18 flashes per second
- Control board with LCD display
- Advantages of LED technology: long life, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- DMX control via every standard DMX controller
- Feed-through output allows to power another device

Logistique

EAN / GTIN: 4026397396034

Poids: 14,30 kg

Longueur: 0.45 m

Largeur: 0.45 m

Hauteur: 0.35 m

Données techniques:

Alimentation électrique: 100-240 V CA, 50/60 Hz

Puissance totale de raccordement: 115,00 W

Type de protection: IP65

Dimension: Largeur : 20 cm

Profondeur : 34,5 cm
Hauteur : 38 cm

Protection grade:	IP65
Beam angle:	40°
LED number:	72
DMX channels:	2/5
DMX connection:	5-pin screw connector
Flash-rate:	18 Hz
Dimensions (L x W x H):	200 x 345 x 380 mm
Weight:	11 kg
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle
