

FUTURELIGHT DMB-150 LED Moving Head

LED beam with 150 W COB LED

Réf. : 51841806

GTIN: 4026397501476



L'article n'est plus disponible.

Caractéristiques:

- Extremely high light output
- Very narrow illumination angle of 5°
- Light beam can easily be centered and moved exactly
- 10, 12, 13 or 16 DMX channels selectable
- Effect wheel with rotating 3-facet prism and 8-facet prism and beam shaper
- Color wheel with 8 different dichroic color filters plus white
- Rainbow effect with adjustable speed in both directions
- Gobo wheel with 11 static gobos plus open
- With gobo shake function
- Exact positioning via 16 bit PAN/TILT movement resolution
- Dimmer
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone
- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Power connection via Neutrik PowerCon jack and included power cable

Logistique

EAN / GTIN: 4026397501476

Poids: 14,35 kg

Longueur: 0.61 m

Largeur: 0.43 m

Hauteur: 0.36 m

- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via any standard DMX controller
- 1 LED puissante
- Gobos
- Effet beam
- L'appareil est refroidi par ventilateur à température contrôlée
- Commandé via DMX; stand-alone; commande de la musique via microphone; RDM
- Déjà préprogrammé pour LED PC-Control 512; Light Captain

Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	195 W
Type de protection:	IP20
Type de lampe:	Lampe LED
Type de LED:	1
Mouvement de basculement max. TILT:	270° positionnement
Mouvement de pivotement max. PAN:	630° positionnement
Équipement:	Gobos
Canaux DMX:	10
Refroidissement:	Ventilateur à température contrôlée
Commande:	DMX; stand-alone; commande de la musique via microphone; RDM
Préprogrammé dans:	LED PC-Control 512; Light Captain
Angle de départ (1/2 pic):	5°
Couleur du boîtier:	Noir
Dimension:	Largeur : 34,3 cm Profondeur : 24 cm Hauteur : 42,8 cm
Poids:	12,05 kg
DMX channels:	10/12/13/16
DMX connection:	5-pin XLR
Sound-control:	via built-in microphone
LED type:	Array 150 W
LED number:	1
Beam angle:	5°
Color-wheel:	8 dichroic filters plus open
Static gobo-wheel:	11 gobos and open
Maximum PAN-movement:	630°
Maximum TILT-movement:	270°
Dimensions (L x W x H):	343 x 250 x 428 mm
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle