

EUROLITE LED FLD-252 6000K 10mm Flood

Compact LED floodlight

Réf. : 51913865

GTIN: 4026397304626



L'article n'est plus disponible.

Description:

Say hello to Mr. Bright!

Difference is everywhere. All wines are not created equal, such are cellphones or is bright light. Concerning the light, this can be demonstrated with our new LED floodlight. As the 252 LEDs know their business, they produce a brightness that has no equal. Whether it is used on stages, at public places or in clubs, our compact floodlight always wins you over. By the way, you can easily adjust the dimmer and strobe functions and via a built-in microphone the movements are sound-controlled. But on account of the ultra bright lights, we recommend to wear sunglasses.

Logistique

EAN / GTIN: 4026397304626

Poids: 4,50 kg

Longueur: 0.54 m

Largeur: 0.23 m

Hauteur: 0.21 m

Caractéristiques:

- Ultra bright white LEDs, 6000 K
- DMX512 control via regular DMX controller (occupies 2 channels)
- Sound-control via built-in microphone
- Adjustable Dimmer and Strobe functions
- Master/Slave function
- Rugged compact housing in a beautiful design
- Ideal for bands, stages or solo entertainers
- Perfect in public places, main halls, lounges
- Mounting bracket for installation on a truss system included
- Advantages of LED technology: long life of the LEDs, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- Commandé via stand-alone; DMX; Commande de la musique via Microphone
- Déjà préprogrammé pour %: Light`J

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	20 W
Type de protection:	IP20
Type de lampe:	Lampe LED
Canaux DMX:	2
Commande:	Stand-alone; DMX; Commande de la musique via Microphone
Préprogrammé dans:	Light'J
Angle de départ (1/2 pic):	30°
Couleur du boîtier:	Noir
Dimension:	Largeur : 45,5 cm Profondeur : 12,5 cm Hauteur : 24 cm
Poids:	4,05 kg
DMX channels:	2
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED number:	252
Beam angle:	30°
Color temperature:	6000 K
Dimensions (L x W x H):	125 x 455 x 240 mm
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle