

## ALUTRUSS Traverse 2 voies E-GL22 4000 BILOCK

Système de traverses 2 points

Réf. : 60302099

GTIN: 4026397572698



### Description:

#### BILOCK E-GL22 2-point truss system

BILOCK E-GL22 is a 2-point truss system made of aluminum. The individual elements are connected via two cones, pivots and pins.

The advantage of the conical connection system is that the cones completely fit into the main chords so that highest load capacity is guaranteed. The Quick-Lock system enables fast, efficient and highly aesthetic assembly when the truss constructions are frequently assembled and dismantled.

The two main chords are made of 50 mm aluminum tube with 2 mm wall thickness and offer a good relation between strength and weight. The braces have a diameter of 20 mm with 2 mm wall thickness and leave enough space for installing couplers, hooks and clamps.

With 290 mm outer dimensions, BILOCK E-GL22 is a stable truss system for higher loads and extended durability. This system is mainly designed for intense use in stage installations, fair installations, event installations but also for permanent installations in discotheques and theatres.

Its polished surface makes this universal system a real eyecatcher. Due to its wide range of standard system lengths, corners, circles and accessory, this system is highly versatile and offers unlimited design possibilities.

The documentation of this truss system is closely related to the Codes of Practice SQ P1 - Truss Systems published by the VPLT/PLASA. The load table as calculation base can be downloaded from the Internet before buying the product!

### Logistique

EAN / GTIN: 4026397572698

Poids: 9,80 kg

Longueur: 4.01 m

Largeur: 0.30 m

Hauteur: 0.06 m

Article encombrant

## Caractéristiques:

---

- Poids réduit
- Assemblage simple
- Tube porteur: 50 mm
- Made in Europe
- Pour des domaines d'application tels que: Théâtre; Agencement de salons et magasin; clubs/écoles de danse
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

## Données techniques:

---

Construction:	Assemblage simple
Tube porteur:	50 mm x 2 mm
Procédé de soudure:	Impulsion WIG
Matière de soudure:	AlMg 5
Matériau du tube:	AISI1MgMn
Couleur:	Couleurs alu
Entretoise diamètre x épaisseur:	20 x 2 mm
Dimension:	Longueur : 400 cm Largeur : 29 cm Hauteur : 5 cm
Poids:	8,90 kg

## Contenu de la livraison:

---

1 x set de connecteurs