



L'articolo non è più disponibile.

Features :

EUROLITE LED PMC-16x20W COB 3200K

PRO COB performance cluster with 4 x 4 matrix

- Equipped with 16 x 20 W COB LED
- 3200 K color temperature
- 3, 16 or 19 DMX channels selectable for various applications
- Each LED can be controlled individually
- Functions: built-in programs and strobe effect with variable speed, dimmer, Master/Slave
- DMX-controlled operation or stand-alone operation with Master/Slave function
- For use on stages, catwalks, crossbeam systems, or decoration
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Locking possibility at the mounting bracket
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- Controllabile via stand-alone; DMX; controllo della musica via microfono
- Già pre-programmato con LED PC-Control 512; Light Captain
- With a beam angle of 60°

Logistica

ROADINGER Flightcase 2x PMC-16

PRO flightcase for 2 x PMC-16

- Compartments for 2 x PMC-16
- Suitable for 41606200 EUROLITE LED PMC-16x20W COB 3200K and 41606400 EUROLITE LED PMC-16x30W COB RGB

- Interior upholstered with foam
- High-quality workmanship with multiplex birch wood, dark brown laminated
- Aluminum profile frames (25 mm) with rounded edges
- Three-leg, large steel ball corners
- 2 hinges
- 2 high-quality butterfly locks
- 2 case handles
- Hardware di marca
- Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica

Dati tecnici :

Peso:	24,60 kg
Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici
Destinazione d'uso:	Illuminazione per effetti speciali

EUROLITE LED PMC-16x20W COB 3200K

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	275 W
Grado di protezione:	IP20
Tipo di lampada:	Lampada a LED
Frequenza di lampeggiamento:	1 - 20 Hz
Canali DMX:	3; 16; 19
Attivazione:	Stand-alone; DMX; controllo della musica via microfono
Pre-programmato con:	LED PC-Control 512; Light Captain
Angolazione del fascio di luce:	60°
Angolazione del fascio di luce (1/2 picco):	60°
Temperatura colore:	3200K
Colore della custodia:	Nero
Misure:	Larghezza: 31,5 cm Profondità: 34,5 cm Altezza: 34,5 cm
Peso:	8,20 kg
DMX channels:	3/16/19
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	20 Hz
Sound-control:	via built-in microphone
LED number:	16
LED type:	Array 20 W, white
Color temperature:	3200 K
Beam angle:	60°
Dimensions (W x D x H):	345 x 315 x 345 mm
Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici

Destinazione d'uso:	Illuminazione per effetti speciali
---------------------	------------------------------------

ROADINGER Flightcase 2x PMC-16

Carico massimo:	50 kg
Uso del marchio:	Hardware di marca
Materiale:	Legno multistrato di betulla, 7 mm
Colore:	Marrone scuro, laminato
Misure:	Larghezza: 39 cm Profondità: 44,5 cm Altezza: 43 cm
Peso:	8,20 kg
Strength:	7 mm
Outside dimensions (W x D x H):	390 x 445 x 430 mm
Inside dimensions (W x D x H):	415 x 355 x 335 mm
Compartment dimensions (W x D x H):	355 x 200 x 335 mm