

OMNITRONIC L-800, Amplifier 2x400W/4 ohm

Reliable PA amplifier for starters

Art.n.: 10450680

GTIN: 4026397243086



Features :

- 2 x 400 W/4 ohms
- Enormous power with highest brilliance
- 2 gain controls on the frontpanel
- All operation modes controllable via LEDs
- Signal inputs via XLR female or 6.3 mm jack socket
- Speaker connection via lockable Speaker plugs
- Ground lift switch against humming
- Bridged switch for bridging
- Protection circuits for optimized equipment protection
- Very rugged housing
- Rack installation

Logistica

EAN / GTIN: 4026397243086

Peso : 11,50 kg

Lunghezza : 0.50 m

Larghezza : 0.43 m

Altezza : 0.10 m

Dati tecnici :

| | |
|----------------------------|---|
| Potenza totale installata: | 1250,00 W |
| Potenza in uscita: | 200 W RMS (8 Ohm) |
| Intervallo di frequenza: | 10 - 50000 Hz |
| Misure: | Larghezza: 48,3 cm Profondità: 35 cm Altezza: 4,45 cm |
| Peso: | 10,30 kg |
| Power supply: | 115/230 AC V AC, 50/60 Hz |

Power output (RMS):

| | |
|----------------------------|---|
| Stereo 4 ohms | 2 x 400 W |
| Stereo 8 ohms | 2 x 200 W |
| 8 ohms bridged | 1 x 800 W |
| Signal-to-noise ratio: | >100 dB |
| Total harmonic distortion: | 0.05 % |
| Damping factor: | >150 |
| Slew rate: | 70 V/ μ sec. |
| Crosstalk: | >70 dB |
| Input impedance: | 20 kohms |
| Input connectors: | 2 x XLR, 2 x Jack mounting socket |
| Output connectors: | 2 x Speaker |
| Protection: | Overheat, overload, short-circuit, DC, softstart |
| Cooling: | Temperature-controlled fan |
| Controls: | Power switch, input attenuators, Mode switch - Stereo/Parallel/Bridged, Ground Lift |
| Indicators: | Power, Clip, Protect, Parallel, Bridge |
| Construction: | Steel chassis, aluminum front panel |
| | Rack installation with 1 u |

Contenuto della confezione: