

OMNITRONIC P-2000 Amplifier, 2x1000W/4ohm

Powerful PA amplifier for large stages

Art.n.: 10451180

GTIN: 4026397145861



Features :

- 2 x 1000 W/4 ohm
- Enormous power with highest brilliance
- 2 gain controls on the front panel
- All operation modes controllable via LEDs
- LED intensity adjustable via brightness control on the rear panel
- Signal inputs via XLR female or 6.3 mm jack socket
- Input sensitivity adjustable via selector on the rear panel
- Speaker connection via lockable Speaker plugs or Banana/screw combination
- With limiter
- Ground Lift switch against humming
- Bridged switch for bridging
- Many protection circuits for optimized equipment protection
- Very rugged housing
- Rack installation
- High power/weight-relation

Logistica

EAN / GTIN: 4026397145861

Peso : 18,50 kg

Lunghezza : 0.51 m

Larghezza : 0.49 m

Altezza : 0.15 m

Dati tecnici :

Alimentazione elettrica: 115/230 V AC, 50/60 Hz

Potenza totale installata: 3500,00 W

Potenza in uscita: 625 W RMS (8 Ohm)

Misure: Larghezza: 48,3 cm
Profondità: 49 cm

| | |
|--------------------------------|--|
| | Altezza: 8,9 cm |
| Peso: | 17,20 kg |
| Power range: | 230 V \pm 10 % (207-253 V) |
| Power output sine: | |
| Stereo 4 ohms | 2 x 1000 W |
| Stereo 8 ohms | 2 x 625 W |
| 8 ohms bridged | 1 x 1875 W |
| Frequency range: | 40-40000 Hz, \pm 3 dB |
| Damping factor: | >400 |
| Distortion factor: | 0.01 % |
| Signal-to-noise ratio: | 90 dB |
| Channel separation (at 1 kHz): | 70 dB |
| Min. input sensitivity: | 0.77 V/26 dB/1.4 V |
| Input impedance: | 20 kohms (balanced) |
| Slew rate: | 60 V/ μ sec |
| Input connectors: | 2 x XLR female plug, 2 x 6.3 mm jack plug |
| Output connectors: | 2 x Speaker (stereo), 1 x Speaker (bridge), 2 x Banana/screw combination |
| Control elements: | Power switch, input attenuators (one per channel), Mode switch - Stereo/Parallel/Bridged, Ground Lift, Input-Level-Select (0.77 V/26 dB/1.44 V), limiter |
| LED indicators (per channel): | Power, Protect, Signal, Mode |
| Protection circuits: | Short-circuit, DCt, thermal, softstart |
| Construction: | Steel chassis, aluminum front panel |
| Minimum mounting depth: | 510 mm |

Contenuto della confezione: