

OMNITRONIC ACS-410BTS Active Column Speaker System

Mobile column PA system with stereo Bluetooth link, 410 W

Art.n.: 11038866

GTIN: 4026397613452



Descrizione :

The ACS-410BTS is an active column PA system with a high-power subwoofer with 2-channel class D amplifier module and a full-range column speaker for mobile applications. The system offers two mono inputs (XLR and 6.3 mm jack) for microphones and line sources, one stereo input (RCA and 6.3 mm jack), as well as one AUX input for portable audio players. You can stream music wirelessly from your mobile devices via Bluetooth. The amplifier supplies a power of 310 W and 100 W and is protected with a limiter against overload. The column speaker mounts on top of the subwoofer with the included telescope bar. The integrated stereo Bluetooth link allows for wireless stereo operation with 2 systems linked together.

Logistica

EAN / GTIN: 4026397613452

Peso : 19,75 kg

Lunghezza : 0.65 m

Larghezza : 0.49 m

Altezza : 0.43 m

Features :

- Highly portable column PA system with 410 watts power
- Clear, dynamic sound and wide coverage for DJs, musicians, presenters and events
- Stereo Bluetooth link for wireless stereo operation with 2 systems linked together
- 10" bassreflex subwoofer with class D amplifiers (310 W + 100 W)
- Column speaker with 6 x 2" drivers
- Integrated Bluetooth audio streaming
- Built-in 6-channel mixer
- 2 mono inputs mic/line with 2-band EQ and adjustable reverb
- 1 stereo line input
- 1 stereo AUX input connects any non-Bluetooth device
- Volume control per channel
- Adjustable monitor output
- Master level control with limiter indication
- Subwoofer with M20 threaded flange and locking features for secure transport of column speaker and distance tube

- MDF enclosures with scratch-resistant lacquer surface, impact-resistant steel grille and carry handles
- Total weight just 18 kg
- Delivery includes variable distance tube, speaker cable and power cable
- Controllabile via Bluetooth

Dati tecnici :

| | |
|----------------------------|---|
| Alimentazione elettrica: | 230 V AC, 50 Hz |
| Potenza totale installata: | 400 W |
| Allacciamento elettrico: | Alimentazione dell'energia elettrica tramite dispositivi a freddo (M) versione da incasso cavo di alimentazione con spina di protezione (in dotazione) |
| Capacità di carico: | Nominale: 100W RMS HF Nominale: 310W RMS LF |
| Intervallo di frequenza: | 45 - 20000 Hz |
| Attivazione: | Bluetooth |
| Collegamenti: | Uscita: Altoparlante via Presa da incasso per altoparlanti (F) Uscita: line via RCA (F) versione da incasso Ingresso: line via 1 x RCA stereo Ingresso: line via 2 x Presa jack (stereo) da 6,3 mm versione da incasso Ingresso: mic/line via 2 x presa combinata XLR a 3 poli/jack da 6,35 mm (F) versione da incasso Ingresso: AUX via 1 x Presa jack (stereo) da 3,5 mm versione da incasso |
| Ingresso canali: | 2 x Stereo with interruttore Mic-Line via Presa combinata (XLR/JACK), channel control via manopola 1 x Stereo via jack, channel control via manopola 1 x Stereo via RCA o jack, channel control via manopola |
| Frequenza di taglio: | 220 Hz |
| Altoparlante: | 1 x 10" Woofer 6 x 2" tweeter |
| Misure: | Larghezza: 33,5 cm Profondità: 41 cm Altezza: 57 cm |
| Peso: | 18,10 kg |

Contenuto della confezione:

- 1 x Cavo di rete/Cavo di alimentazione
- 1 x cavi per altoparlanti
- 1 x bass
- 1 x testata
- 1 x Sostegno
- 1 x Manuale d'uso