

INTUSONIC HZE11+ Zone Remote Control Panel

Flush-mount control panel for HMA7x audio routers, RS485, incl. IR remote control

Art.n.: 12604191

GTIN: 5060502923608



Descrizione :

The INTUGRID HZE11+ comes with an improved design and provides a local control frontend for Intusonic's RS-485 enabled audio control systems. It is the perfect complement for the HMA7x series of audio routers. It fits wall box sizes with minimal depth (86 mm) and hence can be mounted right where it is needed - in the room to be controlled. A standard CAT network cable is sufficient for connections; no additional power supply is required.

Due to its daisy-chaining possibilities, more than one unit can be installed in a room, with the last operated one setting the system, and those settings being replicated on all HZE11+ panels as well as the connected main unit.

A local audio feed is possible via the provided 3.5mm jack for a stereo signal or alternatively via a 6.35mm jack for a mono microphone. The last-selected external audio signal from an HZE11+ panel has priority over other panels in the room, so that their audio signals are ignored and there is no unwanted noise on the audio bus. The previous model did not have this feature. Both models are compatible, but when used in combination with the HZE11, the HZE11+ reverts to the previous functionality.

For enhanced convenience, the HZE11+ also sports an infrared remote control receiver and comes with a IRB44 remote control right out of the box.

Features :

- Extended version, offering last-selected audio priority on the external bus
- Multiple units can be linked
- Montaggio a incasso
- Schermo LCD
- Controllabile via Telecomando IR

Logistica

EAN / GTIN: 5060502923608

Peso : 0,31 kg

Lunghezza : 0.11 m

Larghezza : 0.10 m

Altezza : 0.06 m

Dati tecnici :

Alimentazione elettrica:	12V DC
Grado di protezione:	IP20
Attivazione:	Telecomando IR
Colore della custodia:	Nero
Tipo di display:	Schermo LCD
Collegamenti:	Ingresso: line via Jack da 3,5 mm (stereo) Ingresso: microfono via Presa jack (mono) da 6,3 mm versione da incasso RS 485 via RJ-45 (F) versione da incasso
Profondità di installazione:	30 mm
Struttura della custodia:	Montaggio a incasso
Misure:	Larghezza: 8,6 cm Profondità: 8,6 cm Altezza: 4,2 cm
Peso:	0,28 kg

Contenuto della confezione:

- 1 x Dispositivo
- 1 x telecomando
- 1 x Pila
- 1 x Manuale d'uso