



L'articolo non è più disponibile.

Features :**OMNITRONIC UHF-201 Wireless Mic System 863.010MHz**

Wireless microphone system with UHF PLL technology

- Receiver unit and hand-held microphone with UHF PLL technology
- Operation in the low-interference UHF band
- Parallel operation of up to 4 sets is possible without any interference
- Volume control
- XLR and 6.3 mm output
- Jack cable included
- LEDs for power, carrier and audio signal
- Microphone with mute switch and color indication
- Matching pocket transmitter can be ordered separately
- License-free and approved in the EU
- Direttività: Cardioide
- UHF 863 - 865 MHz registrazione e gratuita in Europa

Dotazione della fornitura

- 1 x microfono

Logistica**OMNITRONIC UHF-200 BP Bodypack 863.010MHz**

Trasmettitore tascabile con microfono lavalier

- Pocket transmitter as UHF PLL system, matching receivers with the same carrier frequency
- Operation in the low-interference UHF band
- Incl. lavalier microphone
- Transmitting power 10 mW
- Sensitivity adjustable

- Power LED
- Mute switch
- Operation via 2 x 1.5 V batteries, type AA
- License-free and approved in the EU
- Direttività: Cardioide
- UHF 863 - 865 MHz registrazione e gratuità in Europa

Dati tecnici :

Peso:	0,83 kg
-------	---------

OMNITRONIC UHF-201 Wireless Mic System 863.010MHz

Tipo:	Set senza fili completo
Potenza totale installata:	10,00 W
Tipo di capsula:	Dinamica
Direttività:	Cardioide
Intervallo di frequenza:	40 - 18000 Hz
Banda di frequenza:	UHF 863 - 865 MHz
Selezione frequenza:	Frequenze uniche
Misure:	Larghezza: 21 cm Profondità: 4,5 cm Altezza: 15,5 cm
Peso:	0,72 kg
Pila:	2 x Mignon (AA) (non in dotazione)
System:	Non-Diversity
Carrier frequency:	863.010 MHz
Coverage:	50 m (with line-of-sight)
RF power output:	10 mW
Modulation method:	F3F
S/N ratio:	>105 dB
Selectivity:	>80 dB
T.H.D.:	<0.5 % at 1 kHz
Audio outputs:	400 mV, 2.2 kohms (XLR, bal.) 200 mV, 2.2 kohms (6.3 mm jack, unbal.)
Power supply	
Receiver:	100-240 V AC, 50/60 Hz via supplied power unit
Dimensions, weight:	
Receiver:	155 x 210 x 45 mm (W x D x H), 1 kg
Microphone:	50 x 265 mm (D x L), 280 g

OMNITRONIC UHF-200 BP Bodypack 863.010MHz

Tipo:	Trasmettitore tascabile con microfono
Tipo di capsula:	Condensatore

Direttività:	Cardioide
Pila:	2 x Mignon (AA) (non in dotazione)
Intervallo di frequenza:	40 - 18000 Hz
Banda di frequenza:	UHF 863 - 865 MHz
Selezione frequenza:	Frequenze uniche
Interruttore:	Interruttori di accensione/spegnimento; interruttore silenzioso
Misure:	Larghezza: 65 cm Profondità: 20 cm Altezza: 2,5 cm
Peso:	0,12 kg
Carrier frequency:	863.010 MHz
Coverage:	50 m (with line-of-sight)
RF power output:	10 mW
Modulation method:	F3F
S/N ratio:	>105 dB
Selectivity:	>80 dB
T.H.D.:	<0.5 % at 1 kHz
Connection:	3.5 mm jack