

ANTARI DarkFX Spot 1750

PRO DMX UV spot with 4 x 16 W UV LED, deep wavelength (365 nm)

Art.n.: 51100823

GTIN: 4719850658144



Descrizione :

The Antari DarkFX Spot 1750 is an efficient high-output and low-power consumption UV LED spot that delivers a peak wavelength of 365 nm and radiant flux output of 19,080 mW at full intensity with minimum visible light. This ensures all UV-reactive materials reflect perfectly with stunningly bright and vivid colors.

Equipped with 4 x 16 W high-power UV LEDs, it features a 20° narrow beam angle, flicker-free operation, and special optics to prevent wear degradation from high UV exposure. This IP20-rated LED spot comes with an aluminium housing with an adjustable bracket for versatile mounting options.

The DarkFX Spot 1750 is operated in one of two modes: Either in DMX mode with 2 channels via the 5-pin XLR connectors or in stand-alone mode via the LCD display and the 4 operating buttons. Use the powerCON input to connect it to the mains.

Features :

- Luce visibile minima
- Alte prestazioni a piena intensità
- Special optics will not degrade due to high UV exposure
- 4 LED 16 W high power ultravioletto (UV)
- Effetto UV
- Controllabile via stand-alone; DMX
- With a beam angle of 20°
- Collegamento a innesto NEUTRIK installato

Logistica

EAN / GTIN: 4719850658144

Peso : 3,85 kg

Lunghezza : 0.35 m

Larghezza : 0.23 m

Altezza : 0.25 m

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	72 W
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite PowerCON (blu), versione da incasso cavo di alimentazione con spina di protezione (in dotazione)
Uscita di corrente:	1 x PowerCON (grigio), versione da incasso
Tipo di lampada:	Lampada a LED
Tipo di LED:	4 x 16 W high power ultravioletto (UV)
Canali DMX:	2
Ingresso DMX:	1 x Versione da incasso XLR (M) a 5 poli
Uscita DMX:	1 x Versione da incasso XLR (F) a 5 poli
Attivazione:	Stand-alone; DMX
Angolazione del fascio di luce (1/2 picco):	20°
Angolazione del fascio di luce (1/10 di picco):	44°
Lunghezza d'onda:	365 nm
Colore della custodia:	Nero
Uso del marchio:	Collegamento a innesto NEUTRIK installato
Peso:	3,26 kg
Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici
Destinazione d'uso:	Illuminazione per effetti speciali

Contenuto della confezione:

1 x Dispositivo
1 x Manuale d'uso
1 x Cavo di rete/Cavo di alimentazione
1 x Staffa di montaggio
2 x vite a testa zigrinata
4 x Rondella