

## EUROLITE LED DL-10-1 3200K 90° Ceiling li LED-downlight

Art.n.: 51935074

GTIN: 4026397285345



**L'articolo non è più disponibile.**

### Descrizione :

Modern and innovative!

Looked at with a critical eye at the beginning, these days LEDs are to be found in many areas and first of all present in a wide range of lamps, where they deeply impress. Whether in moving heads, scanners, flower effects, classic spots, torches, or alternatively in fitted spotlights. A precious, modern, powerful and functional example which represents our EUROLITE LED DL-10-1. With its 10 times 1 watts high performance diodes, which do achieve a color temperature of 3200 Kelvin, the spotlights enrich bars, malls, restaurants or shops and enable innovative illuminating. Especially at trade shows, starry heavens or other interesting installations can be realized. Beside the already known features of the LED-technic, the brightness, the long life expectancy or the low power consumption, the DL-1 can also call attention due to its minimized installation depth. A light so bright, let it shine.

### Features :

- Compact downlight for innovative illumination of bars, malls, restaurants or shops
- LED starlights or fancy fair installations can be realized
- Fixation via clamps
- Long LED life
- Little mounting depth
- Advantages of high-power LED technology: extreme light output, long life, low power consumption, defacto maintenance free
- Installation only by professional installers or electricians

### Logistica

EAN / GTIN: 4026397285345

Peso : 1,35 kg

Lunghezza : 0.27 m

Larghezza : 0.12 m

Altezza : 0.26 m

**Dati tecnici :**

|                            |                                        |
|----------------------------|----------------------------------------|
| Alimentazione elettrica:   | 230 V AC, 50 Hz                        |
| Potenza totale installata: | 29,00 W                                |
| Misure:                    | Profondità: 12 cm<br>Diametro: Ø 23 cm |
| LED number:                | 10 x 1 W                               |
| Beam angle:                | 90°                                    |
| Installation hole:         | 210 mm                                 |
| Minimum mounting depth:    | 120 mm                                 |
| Dimensions (L x W x H):    | 230 x 120 mm                           |
| Weight:                    | 1.3 kg                                 |