

EUROLITE LCD-4/S Dimmer controller

4-channel lighting controller

Art.n.: 70062661

GTIN: 4026397179095



L'articolo non è più disponibile.

Features :

- 4 channels
 - Fade Time fader with LED for adjusting the step time
 - Master-fader with LED for adjusting the total output level
 - Audio-fader with LED for adjusting the music sensitivity
 - Flash-button per channel and master-flash (Full On-button)
 - LED-display of all modes
 - 0/10 V-output via one 8-pin DIN-socket
 - 42 built-in programs
 - Dimmer: Manual control of the channels via sliders
 - Full On: all channels can be switched on together
 - Program speed adjustable via speed-fader or Tap Sync-button
 - Sound-control via external signal or integrated microphone
 - Sound to light via RCA socket
 - Outputs via 4 safety sockets
 - Rack installation with 3 units
 - Only for professional use
- Dispositivo**
- Senza fili, flessibile e versatile
- Dotazione della fornitura**
- 1 x Dispositivo

Logistica

EAN / GTIN: 4026397179095

Peso : 5,15 kg

Lunghezza : 0.52 m

Larghezza : 0.20 m

Altezza : 0.21 m

Dati tecnici :

Alimentazione elettrica:

230 V AC, 50 Hz

Misure:	Larghezza: 48,3 cm Profondità: 14,5 cm Altezza: 13,35 cm
Dispositivo	
Tipo di batteria:	1 x nickel cadmium 3,6 V,
Max. power output:	3680 W
Max. current:	16 A
Number of control channels:	4
Max. output/channel:	1150 W
Max. current/channel:	5 A
Integrated programs:	42
Sound-control:	via built-in microphone or via audio-input
Audio-input:	RCA socket
Audio-sensitivity:	0.1-1 V
Output sockets:	4 safety sockets
Fuse:	4 x F 6.3A, 250 V
Dimensions (W x D x H):	482 x 145 x 132 mm
	Rack installation with 3 u
Minimum mounting depth:	230 mm
Weight:	4.5 kg